

PRODUCT APPLICATION



PROUDLY DESIGNED AND BUILT IN AUSTRALIA

EasyAir 128078-SA Air Transducer for Air Suspension Trailers

- Low Cost Weighing.
- Simple Installation.
- Atmospherically Adjusted.
- Fully Sealed Unit.
- Push in Air Fittings.
- Suit Metric or Imperial Airlines.
- Robust in Design.
- High Accuracy.

Description

The Elphinstone EasyAir is a high quality air transducer unit for on-vehicle weighing of trailers fitted with an air suspension. This unit measures air pressure from both sides of the suspension (giving faster response times) and converts this information into a digital weight display in cabin. Automatically accounts for changes in atmospheric conditions and temperature.

Compatibility. The EasyAir transducer system is compatible with both of Elphinstone's indicator systems (Easyweigh® Radio Remote and D Model Cab Mount indicator systems). EasyAir is also compatible with most other brands of electronics.

Proven Performance. Elphinstone have been designing and installing on-vehicle weighing systems since 1976. We have incorporated the latest technology to assure you of dependable service from our systems.

Specifications

SIZE See Drawing Below

WEIGHT 960 grams (34 oz)

CONNECTION Military connector

CASE Aluminium Case – Powdercoated

MOUNTING BRACKET Aluminium


PRESSURE RANGE 4psi - 150psi

ACCURACY – Transducer +/- 0.5%

ACCURACY – Operational +/- 1% See Below

Accuracy when installed in air suspension is dependent on the following:

- Suspension assembled correctly. Bushes tensioned at correct ride height
- Ride height valve should be fast acting and set at correct height
- Have **NO** air leaks in trailer
- Ensure full air pressure in trailer, this means full tanks, not just enough to release brakes
- Have trailer brakes off whilst loading/reading weights
- Stand trailer on level and flat ground whilst reading weights
- Allow pressure to steady in suspension after adding more load or moving trailer
- Ensure a clean air system
- Driver awareness to these points gives better operational accuracy



Ordering Information



Specifications subject to change without notice

Victorian Office 2/670 Somerville Road Sunshine, VIC 3020 Ph: (03) 9311 6366 Fax:(03) 9311 6466 Email: vic.office@elph.com.au

NSW Office PO Box 319, Riverwood, NSW 2210 Ph: (02) 9584 8550 Fax:(02) 9584 8551 Email: nsw.office@elph.com.au | Email: wa.office@elph.com.au

16 Williams Road, Collie, WA 6225 Ph: (08) 9734 3820 Fax:(08) 9734 2795

WA Office

Head Office Tasman Hwy, Triabunna, TAS 7190 Ph: (03) 6257 3242 Fax:(03) 6257 3573 Email: tri.office@elph.com.au

Internet: www.elph.com.au